




on chart

SELECTING THE CORRECT TARGET SHAFT

Our Target Shaft Selection Chart will help you, quickly and easily, find the perfect shaft match for your bow.

Advanced, interactive Spine Weight Comparison and Hunting Shaft Selection Charts—now available online at www.easton.com.

COMPOUND BOW - Release Aid Calculated Peak Bow Weight - Lbs.			CORRECT ARROW LENGTH FOR TARGET • FIELD • 3D										RECURVE BOW Bow Weight - Lbs. Finger Release			
Soft Cam	Medium Cam	Single or Hard Cam	22½ (57.2 cm)	23½ (59.7 cm)	24½ (62.2 cm)	25½ (64.8 cm)	26½ (67.3 cm)	27½ (69.9 cm)	28½ (72.4 cm)	29½ (75.0 cm)	30½ (77.5 cm)	31½ (80.0 cm)		32"		
			ATA up to 210 FPS IBO up to 260 FPS	ATA 211-230 FPS IBO 261-290 FPS	ATA 231 FPS up IBO 291 FPS up	23½ (59.7 cm)	24½ (62.2 cm)	25½ (64.8 cm)	26½ (67.3 cm)	27½ (69.9 cm)	28½ (72.4 cm)	29½ (75.0 cm)	30½ (77.5 cm)	31½ (80.0 cm)	32½ (82.5 cm)	
29-35 lbs. (13.2-15.9 kg)									T1	T2	T3					17-23 lbs. (7.7-10.4 kg)
35-40 lbs. (15.9-18.1 kg)	29-35 lbs. (13.2-15.9 kg)								T1	T2	T3	T4	T5			24-29 lbs. (10.9-13.2 kg)
40-45 lbs. (18.1-20.4 kg)	35-40 lbs. (15.9-18.1 kg)	29-35 lbs. (13.2-15.9 kg)							T1	T2	T3	T4	T5	T6	T7	30-35 lbs. (13.6-15.9 kg)
45-50 lbs. (20.4-22.7 kg)	40-45 lbs. (18.1-20.4 kg)	35-40 lbs. (15.9-18.1 kg)							T1	T2	T3	T4	T5	T6	T7	36-40 lbs. (16.3-18.1 kg)
50-55 lbs. (22.7-24.9 kg)	45-50 lbs. (20.4-22.7 kg)	40-45 lbs. (18.1-20.4 kg)							T1	T2	T3	T4	T5	T6	T7	41-45 lbs. (18.6-20.4 kg)
55-60 lbs. (24.9-27.2 kg)	50-55 lbs. (22.7-24.9 kg)	45-50 lbs. (20.4-22.7 kg)							T2	T3	T4	T5	T6	T7	T8	46-50 lbs. (20.9-22.7 kg)
60-65 lbs. (27.2-29.5 kg)	55-60 lbs. (24.9-27.2 kg)	50-55 lbs. (22.7-24.9 kg)							T3	T4	T5	T6	T7	T8	T9	51-55 lbs. (23.1-24.9 kg)
65-70 lbs. (29.5-31.8 kg)	60-65 lbs. (27.2-29.5 kg)	55-60 lbs. (24.9-27.2 kg)							T4	T5	T6	T7	T8	T9	T10	56-60 lbs. (25.4-27.2 kg)
70-76 lbs. (31.8-34.5 kg)	65-70 lbs. (29.5-31.8 kg)	60-65 lbs. (27.2-29.5 kg)							T5	T6	T7	T8	T9	T10	T11	61-65 lbs. (27.7-29.5 kg)
76-82 lbs. (34.5-37.2 kg)	70-76 lbs. (31.8-34.5 kg)	65-70 lbs. (29.5-31.8 kg)							T6	T7	T8	T9	T10	T11	T12	66-70 lbs. (29.9-31.8 kg)
82-88 lbs. (37.2-39.9 kg)	76-82 lbs. (34.5-37.2 kg)	70-76 lbs. (31.8-34.5 kg)							T7	T8	T9	T10	T11	T12	T13	71-76 lbs. (32.2-34.5 kg)

No X10 or A/C/E shafts suitable in shaded areas above.

Size	Spine	Model	Weight Grs/inch	Wt @29"	Size	Spine	Model	Weight Grs/inch	Wt @29"	Size	Spine	Model	Weight Grs/inch	Wt @29"	Size	Spine	Model	Weight Grs/inch	Wt @29"
Group T1					Group T2					Group T3					Group T4				
*920•1000R	0.920•1.000	A/C/E	5.8	168	*780•850R	0.780•0.850	A/C/E	6.0	174	*720•780R	0.720•0.780	A/C/E	6.4	186	*670•720R	0.670•0.720	A/C/E	5.9	171
*900•1000R	0.900•1.000	X10	5.8	168	*750•830R	0.750•0.830	X10	6.4	186	*700•750R	0.700•0.750	X10	6.7	194	*650•700R	0.650•0.700	X10	6.8	197
*880•1000R	0.880•1.000	Nav	5.5	160	*810•880R	0.810•0.880	Nav	5.8	168	*710•810R	0.710•0.810	Nav	6.3	183	*660•710R	0.660•0.710	Nav	6.6	191
2L-04	1.020	A/C/C	6.1	177	2-04	0.920	A/C/C	6.5	189	3X-04	0.850	A/C/C	6.7	194	3L-04	0.750	A/C/C	7.0	205
2-04	0.920	A/C/C	6.5	189	780	0.780	Rdln	6.3	183	3L-04	0.750	A/C/C	7.0	203	3-04	0.680	A/C/C	7.2	209
900	0.900	Rdln	5.8	168	1812	0.879	X7	7.3	212	780	0.780	Rdln	6.3	183	690	0.690	Rdln	6.3	183
1712	1.099	X7	6.7	194	1714	0.963	X7	8.1	235	1912	0.778	X7	7.6	220	1912	0.778	X7	7.6	220
1713	1.044	X7	7.4	215	1716	0.880	75	9.0	261	1813	0.874	75	7.9	229	2012	0.788	X7	8.0	232
1714	0.963	X7	8.1	235						1814	0.799	X7	8.6	249	1913	0.733	75	8.3	241
1616	1.079	75	8.4	244						1816	0.756	75	9.3	270	1914	0.658	X7	9.3	270
Group T5					Group T6					Group T7					Group T8				
*620•670R	0.620•0.670	A/C/E	6.1	177	*570•620R	0.570•0.620	A/C/E	6.3	183	*520•570R	0.520•0.570	A/C/E	6.7	194	*470•520R	0.470•0.520	A/C/E	6.8	197
*600•650R	0.600•0.650	X10	7.0	203	*550•600R	0.550•0.600	X10	7.5	218	*500•550R	0.500•0.550	X10	7.8	226	*450•500R	0.450•0.500	X10	8.1	235
*610•660R	0.610•0.660	Nav	6.9	200	*540•610R	0.540•0.610	Nav	7.4	215	*540•610R	0.540•0.610	Nav	7.4	215	*480•540R	0.480•0.540	Nav	8.0	232
3-04	0.680	A/C/C	7.2	209	500	0.500	AC Slim	8.5	247	500	0.500	AC Slim	8.5	247	500	0.500	AC Slim	8.5	247
690	0.690	Rdln	6.3	183	3L-18	0.620	A/C/C	7.5	218	3-18	0.560	A/C/C	7.8	226	3-28	0.500	A/C/C	8.1	235
2012	0.680	X7	8.0	232	600	0.600	Rdln	6.9	200	3-28	0.500	A/C/C	8.1	235	3-39	0.440	A/C/C	8.6	249
2013	0.610	75	9.0	261	500	0.500	LSpd	6.5	189	520	0.520	Rdln	7.1	206	460	0.460	Rdln	7.3	212
1914	0.658	X7	9.3	270	500	0.500	FB	7.1	206	500	0.500	LSpd	6.5	189	500	0.500	LSpd	6.5	189
1916	0.623	75	10.0	290	2112	0.590	X7	8.4	244	500	0.500	FB	7.1	206	500	0.500	FB	7.1	206
					2013	0.610	75	9.0	261	2212	0.505	X7	8.8	255	2212	0.505	X7	8.8	255
					2014	0.579	X7	9.6	278	2114	0.510	X7, 75	9.9	287	2213	0.460	X7, 75	9.9	287
					1916	0.623	75	10.1	290	2016	0.531	75	10.6	307	2114	0.510	X7, 75	9.9	287
															2115	0.461	75	10.8	313
Group T9					Group T10					Group T11					Group T12				
*430•470R	0.430•0.470	A/C/E	7.0	203	*400•430R	0.400•0.430	A/C/E	7.5	218	*370•400R	0.370•0.400	A/C/E	7.9	229	370R	0.370	A/C/E	7.9	229
*410•450R	0.410•0.450	X10	8.5	247	*380•410R	0.380•0.410	X10	8.9	258	380R	0.380	X10	8.9	258	340	0.340	AC Slim	10.7	310
*430•480R	0.430•0.480	Nav	8.4	244	*430•480R	0.430•0.480	Nav	8.4	244	400	0.400	AC Slim	9.7	281	3-60	0.340	A/C/C	9.5	276
400	0.400	AC Slim	9.7	281	400	0.400	AC Slim	9.7	281	3-49	0.390	A/C/C	8.8	255	3-71	0.300	A/C/C	9.9	287
3-39	0.440	A/C/C	8.6	249	3-39	0.440	A/C/C	8.6	249	3-60	0.340	A/C/C	9.5	276	360	0.360	Rdln	8.3	241
460	0.460	Rdln	7.3	212	3-49	0.390	A/C/C	8.8	255	360	0.360	Rdln	8.3	241	340	0.340	LSpd	8.2	238
400	0.400	LSpd	7.4	215	410	0.410	Rdln	7.6	220	400	0.400	LSpd	7.4	215	340	0.340	FB	8.3	241
400	0.400	FB	7.8	226	400	0.400	LSpd	7.4	215	400	0.400	FB	7.8	226	2512	0.321	X7	10.3	299
2312	0.423	X7	9.5	276	400	0.400	FB	7.8	226	2413	0.365	X7, 75	10.5	305	2613	0.265	X7	11.5	334
2213	0.460	X7, 75	9.9	287	2412	0.400	X7	9.7	281	2314	0.390	X7, 75	10.8	313					
2214	0.425	X7	10.4	302	2413	0.365	X7, 75	10.5	305	2315	0.340	X7, 75	11.8	342					
2115	0.461	75	10.8	313	2214	0.425	X7	10.4	302										
					2314	0.390	X7, 75	10.8	313										
Group T13					Group T13														
300	0.300	AC Slim	11.5	334	2613	0.265	X7	11.5	334										
3-71	0.300	A/C/C	9.9	287															
2512	0.321	X7	10.3	299															
2613	0.265	X7	11.5	334															

* When two sizes are listed together, the weight listed is for the first shaft.

A/C/E Aluminum/Carbon/Extreme
X10 X10 Shafts (Aluminum/Carbon)
Nav Navigator (Aluminum/Carbon)
AC Slim Aluminum/Carbon Super Slim
A/C/C Aluminum/Carbon/Composite
Rdln Redline
LSpd LightSpeed
FB FatBoy
X7 X7 Eclipse and Cobalt (7178-79 alloy)
75 XX75: Platinum Plus and Jazz (7075 alloy)

R The size recommendations for recurve bows are indicated with a letter "R" next to the size.
Size Indicates suggested arrow size
Spine Spine of arrow size shown (static)
Model Designates arrow model
Weight Listed in grains per inch